

SANARG 180AP

TIG Arc Welding

Processes
AC/DC HF-Start/L-TIG/
STICK

Product Number
IAU-W180AP-U1DVP

Input Voltage
120/208-240 VAC 1 Phase
Rated Output
140A @ 40% Duty Cycle (120V)
200A @ 25% Duty Cycle (240V)

Output Range
DC = 5 - 200A/AC = 10 - 200A (240vac)
DC = 5 - 140A/AC = 10 - 140A (120vac)
Input Frequency **Weight**
50/60 Hz. 24.7lbs (11.2 kg)

The SanRex 180AP is a dual-voltage, AC/DC L-TIG & HF-TIG/STICK welding power supply. Includes Pulser, AC frequency, AC Balance, Shielding gas Solenoid with Pre and post flow timer.

Features:

- **Exceptional Performance:** Delivering perfectly smooth, stable arc characteristics.
- **HF Start TIG:** Provides non-contact arc starting that eliminates tungsten or material contamination.
- **Lift Start TIG:** Provides TIG arc starting without use of High Frequency.
- **Auto Switch:** Multi-voltage 120/208-240 vac, single phase.
- **Certifications:** CSA, IEC-974
- **PFC Power Factor correction:** Up to 40% more electrically efficient than conventional MIG Welders.


**Compact and Portable
AC/DC Welding Inverter**



Ordering Information

Product	Part Number	Description
SANARG 180AP Pkg.	IAU-W180AP-U1DVP	Includes 180AP Power Supply, TIG Torch with torch mounted remote control & Accy pkg., Regulator/ Flowgauge with Gas Hose, 8ft. Work Lead and Electrode Holder, 120/240 vac adaptor.

Accessories

 Foot Control	FC2000	Remote Foot Control with On/Off and current control.
--	--------	--

SanRex

Customer Care
Tel: 516-625-1313
Fax: 516-625-8845

SANREX CORPORATION
PORT WASHINGTON, NY, USA

www.sanrex.com
SANSTICK 180AP
Form No.:012220180AP